

NEUTRONLUB

THE BEST HI-TECH FLUID & COMPOUNDS - USA

Multi-Purpose Calcium Chassis Grease - Tacky

Multipurpose chassis grease with tackiness agent.

Working temperature below 70°C. Dropping point 102°C.

Designed primarily for chassis lubrication of automotive, tractors, farm and earth moving equipments, in both commercial and passenger car industries.

Excellent for chassis points, shackles, bushings, clutch throw out bearings and similar applications. Also found to be used in industrial bearings and general purpose plant operations.

## **TECHNICAL INFORMATION**

Z

0

-

4

 $\geq$ 

22

0

LZ

0

D

0

P X

4

0

2

T

0

Ш

	ASTM TEST	RESULT
N.L.G.I. Grade	D – 942	2 & 3
Penetration worked	<b>D</b> – 217	275 - 290
Viscosity		
@ 40 °C cSt	<b>D</b> – 445	225
@100 °C cSt	<b>D</b> – 445	18.5
Dropping Point	<b>D</b> – 2265	102
Flash Point	<b>D</b> – 92	221
Timken O.K. Load	D – 2509	45
Color	D – 1500	Brown
Thickener		Calcium anhydrous

## **NEUTRON FLUID & COMPOUNDS DIVISION**

Value shown here are typical and may vary. NEUTRON FLUID & COMPOUNDS DIVISION reserves the right to change or modify this product for purpose of improving its performance characteristics.

© 1998 Copyright Reserved

## FHE BEST HI-TECH FLUID & COMPOUNDS - US